

Lärmemission Fronius Primo GEN24

Fronius International GmbH

bestätigt die folgenden Parameter:

	Typischer Schalleistungspegel ref. 1 pW	Typischer Schalldruckpegel ref. 20 µPa	Maximaler Schalldruckpegel ref. 20 µPa
Fronius Primo GEN24 8.0 – 10.0	57,4 dB(A)	50,4 dB(A)	50,6 dB(A)

Die typischen Schallwerte (Schalleistung / Schalldruck) wurden bei maximaler Last und einer Umgebungstemperatur von 25°C ermittelt, während der maximale Schalldruckpegel den größten vom Wechselrichter erzeugten Schalldruck darstellt.

Die Schalleistung ist die Summe des über die gesamte Oberfläche des Geräts abgestrahlten Lärms.

Der Schalldruckpegel wird in 1 m Entfernung vor dem Gehäuse gemessen und stellt die Lärmbelastung an dieser Stelle unter bestimmten Umgebungsbedingungen dar.

Fronius International GmbH

Business Unit Solar Energy
Froniusplatz 1
4600 Wels



FRONIUS INTERNATIONAL GMBH
Froniusplatz 1, A-4600 Wels
Tel: +43(0)7252/241-0, Fax: 241-3013

Philipp Rechberger
Head of System Technology

Noise Emission Fronius Primo GEN24

Fronius International GmbH

confirms the following acoustic parameters:

	Typical Sound Power ref. 1 pW	Typical Sound Pressure ref. 20 µPa	Maximum Sound Pressure ref. 20 µPa
Fronius Primo GEN24 8.0 – 10.0	57.4 dB(A)	50.4 dB(A)	50.6 dB(A)

The typical sound values (sound power / sound pressure) were determined at maximum load and an ambient temperature of 25°C, while the maximum sound pressure level represents the highest sound pressure generated by the inverter.

The sound power is the sum of the noise emitted over the entire surface of the device.

The sound pressure level is measured at a distance of 1 m in front of the housing and represents the noise pollution at this point under certain environmental conditions.

Fronius International GmbH

Business Unit Solar Energy

Froniusplatz 1

4600 Wels



Fronius
FRONIUS INTERNATIONAL GMBH
Froniusplatz 1, 4600 Wels
Tel: +43 (0)7242 241-0, Fax: 241-3013

Philipp Rechberger

Head of System Technology